

CONTENTS

Petrinin V. F. *The Nanotechnologies of Nanomaterials* 2
Perspectives of ultra disperse (nano-) powders for the nanotechnologies development in Russia.

Nazarenko V. A. *Neutron Methods on Investigation of Structure and Properties of Materials* 4
This article considers the properties of neutron radiation and the field of its application in fundamental science and applied research. The present status of the construction works of the high-flux research reactor PIK is described.

Chaplygin Yu. A. *Problems of Specialists Training for Nanotechnology Development and Nanostructures Production* 8
The features of training of specialists at nanotechnologies in Russian Federation are considered.

Bykov V. A. *The Nanoelectronics Manufacturing Basis Development in Zelenograd* 11
We consider on development and production of scanning probe microscopes and accessories for nanotechnologies.

Axenov A. I., Bobrinetskii I. I., Nevolin V. K., Simunin M. M. *Carbon Nanotube Bundle Chemical Sensors for Low Concentration of Chlorine Molecules Detection in Air* 12
The electrical characteristics of carbon nanotube bundle structure placed in air containing chlorine molecules was studied. It was shown the structure conductivity increases by up to an order of magnitude when chlorine concentration changes by 0.5 ppm.

Kozlov A. G. *Modelling of Non-Steady Operating Mode of Thermal Cantilever Radiation Microsensor* 16
An analytical method is presented that allows one to model the non-steady operating mode of the thermal cantilever radiation microsensor. In the microsensor, two regions with equivalent parameter are marked out. For each region the non-steady-state heat conduction equation is obtained that is solved by means of the Fourier integral transform by time. The heat flux density between the regions is determined using an adjoint boundary condition. The analytical expression for the frequency response of the thermal subsystem of the microsensor is obtained. Based on the presented method, for the concrete thermal cantilever radiation microsensor the modulus and the angle of the frequency response and the time dependencies of the temperature of hot thermojunctions for the step, harmonic and impulse input actions are determined.

Panfilov Yu. V. *Nanostructured Materials and Nanotechnology: State of the Art. Part II* 26
Analysis of "7th International Conference on Nanostructured Materials" proceedings as well as state of the art in the nanostructured materials and nanotechnology field are carried out. The main attention is paid to chances and risks of activities in the nanostructured materials and nanotechnology fields.

Gordeev S. K., Korchagina S. B., Lamanov A. M., Lamanov M. M., Moia A. M., Slepnev S. P., Sheshin E. P. *New Method for Preparation the Field Emission Cathodes from Graphite Foil* 33
At this paper investigation results of emission properties field cathodes are presented. These cathodes were made of graphite foil. The emission centers on the foil surface were produced by the laser radiation. Threshold field strength of cathodes is under 3 V/ μm .

Adamov Yu. F., Gubin Ya. S., Kokin S. A., Makarov S. V., Somov O. A. *Abstract to Article "Parametrisation and Verification of Analog Blocks for "System on Chip" when Changing Technology"* 37
New parametrisation methods for analog and analog-to-digital blocks by way of the scale transformation when changing specification or fabrication technology have been offered. Functional verification of scaled blocks is executed taking into account parasitic capacitances and resistances of conductors. For acceleration of modeling extractions automatic simplification of the scheme is used, reducing number of parasitic elements. Adequacy of the applicable transformations is checked on example of programmed high-frequency clock oscillator IP-block.

Barabanenkov M. Yu., Starkov V. V. *Micromirrors from Periodical Two Dimensional Metal-Dielectric Hollow Pins* 40
Two dimensional square lattice of hollow silicon dioxide pins is fabricated by a method of macroporous silicon microstructuring. It is proposed to form metal-dielectric structures by metallization of the inner surface of the hollow pins. Mid-infrared reflection and transmission spectra are computed for dielectric and metal-dielectric structures. A dependence of photonic band gap spectral width and magnitude is investigated upon wall thickness of the dielectric pins. It is shown that square lattice of metal-dielectric two-wall pins can function as beam splitter and micromirrors with high reflectivity.

Osipov L. V. *The Electronics of Medicine* 45
Perspectives the Electronics of Medicine use, which is the direction of developed of Russia.

For foreign subscribers:

"NANO and MICROSYSTEMS TECHNIQUES" Magazine (Nano- i mikrosistemnaa tehnika, ISSN 1684-6419)
Joint-stock company MK-Periodica. E-mail: info@periodicals.ru Tel.: +7(095) 684-5008. Fax: +7(095) 681-3798

The journal bought since november 1999.
Editor-in-Chief Ph. D. Petr P. Maltsev
ISSN 1813-8586.

Address is: 4, Stromynsky Lane, Moscow, 107076, Russia. Tel./Fax: +7(095) 269-5510.
E-mail: it@novtex.ru; <http://www.microsystems.ru>

Адрес редакции журнала: 107076, Москва, Стромьинский пер., 4/1. Телефон редакции журнала (095) 269-5510. E-mail: it@novtex.ru
Журнал зарегистрирован в Федеральной службе по надзору за соблюдением законодательства в сфере массовых коммуникаций и охране культурного наследия.
Свидетельство о регистрации ПИ № 77-18289 от 06.09.04.

Дизайнер Т.Н. Погорелова. Технический редактор И.С. Павлова. Корректор Е. В. Комиссарова

Сдано в набор 03.10.2005. Подписано в печать 11.11.2005. Формат 60×88 1/8. Бумага офсетная. Печать офсетная.
Усл. печ. л. 6,86. Уч.-изд. л. 7,93. Заказ 2010. Цена договорная

Отпечатано в Подольской типографии — филиал ОАО "ЧПК", 142110, г. Подольск, ул. Кирова, 15